



HGL Industrial

Product Data Sheet

Products for Industry, Office & Home

INDUSTRIAL

HG Laboratories, LLC
657 South Hurstbourne Parkway
Suite 284
Louisville, KY 40222
(502) 468-3465
www.hglindustrial.com

Prevox 5000

Water Displacing Rust Preventative

Prevox 5000 is a solvent-based, water displacing rust preventative and is suitable for indoor protection only. After application the solvent evaporates, leaving a thin, translucent film that remains flexible, thus providing protection to all surfaces. **Prevox 5000** rust preventative is clear and essentially not discernible and, for many types of finished parts, does not require removal. **Prevox 5000** rust preservative is especially recommended for use on parts in process. During machining, sub-assembly, storage, inspection, etc., a machined part typically is exposed to moisture, machinists' fingerprints, and corrosive atmospheres such as acid, or caustic fumes from pickling baths and degreasing, or other operations.

Advantages and Benefits :

Fingerprint-neutralizing—When applied to surfaces freshly marked with fingerprints, it prevents the staining that otherwise would occur.

Water-displacing properties - When it is applied to surfaces wet with water or emulsions, it displaces the water from the surfaces.

The thin film formed by the rust preventative minimizes buildup, therefore it can be applied periodically to protect the finished steel.

Physical Characteristics

TEST	RESULTS
Specific Gravity	0.816
Flash Point F	146
Boiling Point	410°F
pH (Concentrate)	N/A
Appearance	Amber liquid
Odor	Mild Solvent

Available packages:
1 gallon bottle-4/case
5 gallon pail
55 gallon drum
275 gallon bulk tank